

Package C: Supply of Computer Peripherals and Maintenance for FY 2019-20

| SN | Particulars | Specification | UNIT | Rate | Remarks |
|----|-------------|--|---------|------|---------|
| 1 | Laptop | Low End Laptop | Per Set | | |
| | | • 5th Generation Intel Core i3- 5005U GHz, 3 MB cache, 2 cores Cache processor | | | |
| | | • 4 GB DDR3L-1600 SDRAM (1 x 4 GB) Memory | | | |
| | | • 500GB 5400 rpm SATA Hard Drive | | | |
| | | • Video graphics: Intel® HD Graphics 5500 | | | |
| | | • Optical DVR-RW drive | | | |
| | | • VGA display adaptor | | | |
| | | • 4-6 USB ports | | | |
| | | • Integrated HD audio system | | | |
| | | • Integrated 10/100 BASE-T Ethernet LAN | | | |
| | | • Wireless connectivity: 802.11b/g/n (1x1) and Bluetooth® 4.0 combo; WiDi | | | |
| | | • SuperMulti DVD burner; optical drive | | | |
| | | • Standard keyboard & mouse | | | |
| | | • Display: 15" diagonal HD SVA BrightView WLED-backlit (1366 x 768) | | | |
| | | • Genuine Microsoft Windows 10 32/64 bit | | | |
| | | • Pre-installed MS Word 2012 | | | |
| | | • Pre-installed Microsoft Security Essentials | | | |
| | | • AC-DC adaptor | | | |
| | | • Carry case bag | | | |

| Mid End Laptop |
|--|
| 5th Generation INTEL® CORE™ I5-6200U (2.3 GHZ, UP TO 2.8 GHZ, 3 MB CACHE, 2 CORES) |
| • 4 GB DDR4-2133 SDRAM (1 X 4 GB) Memory |
| • 750 SATA Hard Drive |
| • VIDEO GRAPHICS: INTEL® HD GRAPHICS 520 |
| • Optical DVR-RW drive |
| • VGA display adaptor |
| • 6-8 USB ports |
| • Integrated HD audio system |
| • 1Gigabit Ethernet Adaptor |
| • 802.11B/G/N (1X1) AND BLUETOOTH: Wireless connectivity |
| • Standard board & mouse |
| • 14" DIAGONAL HD SVA BRIGHTVIEW WLED-BACKLIT (1366 X 768) wide Screen |
| • AC-DC pow Genuine Microsoft Windows 10 32/64 bit |
| • Pre-installed MS Word 2012 |
| • Pre-installed Microsoft Security Essentials |
| • AC-DC adaptor |
| • Carry case bag |

[illegible]

| | | | | | |
|---|--------------------|---|--|--|--|
| 2 | Desktop All in one | 7th Generation Intel Core i3-7100U Processor (3M Cache, 2.40 GHz) | | | |
| | | 8GB 2400MHz DDR4 up to [16GB], (additional memory sold separately) | | | |
| | | 1 TB 5400 RPM [SATA] (HDD) , Tray load DVD Drive (Reads and Writes to DVD/CD) | | | |
| | | 23.8-inch FHD (1920 x 1080) True-life LED-Backlit Touch Display with Wide Viewing Angle | | | |
| | | Intel HD Graphics 620 | | | |
| | | Number of USB 2.0 Ports: 2 | | | |
| | | Number of USB 3.0 Ports: 2 | | | |
| | | Genuine Windows 10 Pro 64-Bit English | | | |
| | | Pre- installed MS word 2016 | | | |
| | | Pre- installed microsoft security Essential | | | |
| | | 1 Year warranty | | | |

| | | | | | |
|---|---------|--|---------|--|--|
| 3 | Printer | Low end printer | Per Set | | |
| | | • Printing Technology: Laser | | | |
| | | • Print, Copy, Scan | | | |
| | | • Standard Memory(MB): 128MB | | | |
| | | • Copier features: Monochrome Copy Speed (PPM-A4) Up to 20 cpm | | | |
| | | • Scanner Features: | | | |
| | | • Scanner Type: Flatbed | | | |
| | | • File Format: Windows & Mac Scan Software supports file format: JPG, RAW (BMP), PDF, TIFF, PNG; | | | |
| | | • Standard paper tray | | | |
| | | • Media sizes supported: A4 | | | |
| | | • Duty Cycle(Pages per month): 8000 | | | |
| | | • USB Port: Yes | | | |
| | | • Network Ready: Yes,Standard (built-in Ethernet, WiFi 802.11b/g/n) | | | |
| | | • WiFi / Bluetooth Support: Yes, built-in WiFi 802.11b/g/n | | | |
| | | • Dimensions (W x D x H): 420 x 365 x 254 mm | | | |
| | | • USB cable, Power code, printer driver, software CD with accessories | | | |
| | | • Supports OS: Windows 7/8/10 32/64 bits | | | |

| | | | | |
|--|--|---|--|--|
| | | High end printer | | |
| | | • Duplex printing automatic (standard) | | |
| | | • Memory, standard: 256 MB | | |
| | | • Standard paper tray | | |
| | | • Media sizes supported: A4 | | |
| | | • Processor speed: 800 MHz | | |
| | | • Print technology: Laser | | |
| | | • First page out (ready): Black: As fast as 6.4 sec | | |
| | | • Recommended monthly page volume: 250 to 2500 | | |
| | | • Connectivity, standard: 1 Ethernet 10/100Base-TX | | |
| | | • Scanner type: ADF, Flatbed | | |
| | | • Scan file format: JPG, RAW (BMP), PNG, TIFF, PDF | | |
| | | • Copier: Copy speed (normal) Black: Up to 28 cpm 17 | | |
| | | • maximum: Up to 99 copies | | |
| | | • USB cable, Power code, printer driver, software CD with accessories | | |
| | | • Supports OS: Windows 7/8/10 32/64 bits | | |

| | | | | | |
|---|--------------------|---|---------|--|--|
| 4 | Heavy duty printer | Copier Specification | Per Set | | |
| | | • Copying process: Laser electrostatic image transfer | | | |
| | | • Copy/print speed: Up to 22 ppm | | | |
| | | • Autoduplex | | | |
| | | • Warm-up time: less than 15 sec | | | |
| | | • Copy resolution: 600 x 600 dpi | | | |
| | | • Original format: A5-A3 | | | |
| | | Printer specification | | | |
| | | • Print resolution (dpi): GDI: 600 x 600 dpi | | | |
| | | • Print functions: n-up; watermark; secure print; image rotation | | | |
| | | Scanner specification | | | |
| | | • Scan resolution (dpi): Max. 600 x 600 dpi | | | |
| | | • Scan modes: Local TWAIN scan, Scan-to-USB | | | |
| | | • File formats: PDF; JPEG; TIFF | | | |
| | | System specification | | | |
| | | • System memory standard (MB): 128 MB | | | |
| | | • Interfaces standard: USB 2.0, 10Base-T/100Base-TX Ethernet | | | |
| | | • Network protocols: TCP/IP (IPv4; IPv6); HTTP; SNMP | | | |
| | | • Paper size: A5 – A3, Customized: 90-297 x 140-432 mm | | | |
| | | • Paper input capacity (sheets): Standard: 350 sheets; max.: 1,350 sheets | | | |
| | | • Automatic duplexing: Yes | | | |
| | | • Copy/print volume max. (monthly): 15,000 pages | | | |
| | | • USB cable, Power code, printer driver, software CD with accessories | | | |
| | | • Supports OS: Windows 7/8/10 32/64 bits | | | |

| | | | | | |
|---|------------------|--|---------|--|--|
| 5 | Managable switch | • Interfaces: 24 x 10Base-T/100Base-TX - RJ-45 - PoE; 1 x console - 9 pin D-Sub (DB-9) - management; 4 x 10Base-T/100Base-TX/1000Base-T - RJ-45; 2 x SFP (mini-GBIC) | Per Set | | |
| | | • Device Type: Switch - 24 ports - L3 - managed | | | |
| | | • Power Over Ethernet : PoE | | | |
| | | • Cables Included: 1x Serial Cable | | | |
| | | • Authentication Method: Secure Shell (SSH), RADIUS, TACACS+ | | | |
| | | • Flash Memory: 16 MB | | | |
| | | • RAM: 128 MB | | | |
| | | • Minimum Storage Temperature: -4 F | | | |
| | | • Status Indicators: Link activity, port transmission speed, system | | | |
| | | • MAC Address Table Size: 16k entries | | | |
| | | • Capacity: 4K Active VLANs | | | |
| | | • Ports: 24 x 10/100 + 2 x combo Gigabit SFP + 2 x 10/100/1000 | | | |

| | | | | | |
|---|---|---|---------|--|--|
| 6 | Unmanagable switch | • Subtype: Gigabit Ethernet | Per Set | | |
| | | • Ports: 24 x 10/100/1000 + 2 x SFP | | | |
| | | • Status Indicators: Link activity, system | | | |
| | | • Cabling Type: Ethernet 1000Base-T, Ethernet 100Base-TX, Ethernet 10Base-T | | | |
| | | • Features: MDI/MDI-X switch, auto-negotiation | | | |
| | | • Compliant Standards: IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x | | | |
| | | • Ports Qty: 24 | | | |
| | | • Communication Mode: full-duplex, half-duplex | | | |
| | | • Type: SFP (mini-GBIC) | | | |
| 7 | Access point (300Mbps Wireless N Access Point | • 300Mbps wireless speed ideal for smooth HD video, voice streaming and online gaming | Per Set | | |
| | | • Supports multiple operation modes: Access Point, Multi-SSID, Client, Universal/WDS Repeater, Bridge with AP | | | |
| | | • Easily setup a WPA encrypted secure connection at a push of the WPS button | | | |
| | | • Up to 30 meters (100 feet) of flexible deployment with included Passive Power over Ethernet Injector | | | |
| 8 | Access point (LINKSYS WAP300N N300 DUAL) | • 4-in-1 product to customize your wireless expansion | Per Set | | |
| | | • Up to N300 Mbps speed* | | | |
| | | • Selectable dual band | | | |
| | | • 1 Fast Ethernet 10/100 port | | | |
| | | • Two antennas for expanded wireless coverage | | | |

| | | | | | |
|---|---|---|---------|--|--|
| 9 | Router(Cisco Catalyst 3750X Stackable 24-Port Switch) (Includes installation and configuration) | <ul style="list-style-type: none"> • 24 and 48 10/100/1000 PoE+, non-PoE models, and 12 and 24 GE SFP port models | Per Set | | |
| | | <ul style="list-style-type: none"> • 24 and 48 10/100/1000 UPOE-capable models with Energy Efficient Ethernet (EEE) support | | | |
| | | <ul style="list-style-type: none"> • Four optional uplink network modules with GE or 10GE ports | | | |
| | | <ul style="list-style-type: none"> • Industry first PoE+ with 30W power on all ports in 1 rack unit (RU) form factor | | | |
| | | <ul style="list-style-type: none"> • Dual redundant, modular power supplies and fans | | | |
| | | <ul style="list-style-type: none"> • Media Access Control Security (MACsec) hardware-based encryption | | | |
| | | <ul style="list-style-type: none"> • Flexible NetFlow and switch-to-switch hardware encryption with the Service Module uplink | | | |
| | | <ul style="list-style-type: none"> • Open Shortest Path First (OSPF) for routed access in IP Base image | | | |
| | | <ul style="list-style-type: none"> • IPv4 and IPv6 routing, Multicast routing, advanced quality of service (QoS), and security features in hardware | | | |
| | | <ul style="list-style-type: none"> • Enhanced limited lifetime warranty (LLW) with next business day (NBD) advance hardware replacement and 90 day access to Cisco Technical Assistance Center (TAC) support | | | |
| | | <ul style="list-style-type: none"> • Enhanced Cisco EnergyWise for operational cost optimization by measuring actual power consumption of the PoE devices, reporting, and reducing energy consumption across the network | | | |
| | | <ul style="list-style-type: none"> • USB Type-A and Type-B ports for storage and console respectively and an out-of-band Ethernet management port | | | |

| | | | | | |
|----|---|---|---------|--|--|
| 10 | Cisco RV320 Dual Gigabit WAN VPN Router | <ul style="list-style-type: none"> • Dual WAN: Dual Gigabit Ethernet Ports, Failover, Load balancing | Per Set | | |
| | | <ul style="list-style-type: none"> • Standards: 802.3, 802.3u, IPv4 (RFC 791), IPv6 (RFC 2460) | | | |
| | | <ul style="list-style-type: none"> • WAN connectivity: Dynamic Host Configuration Protocol (DHCP) server, DHCP client, DHCP relay agent, Static IP, Point-to-Point Protocol over Ethernet (PPPoE), Point-to-Point Tunneling Protocol (PPTP), IPv6, DNS relay, Dynamic DNS (DynDNS.org, 3322.org), DNS local database | | | |
| | | <ul style="list-style-type: none"> • Routing protocols: Routing Information Protocol (RIP) v1 and v2, and RIP for IPv6 (RIPng), Inter-VLAN routing, Static routing, VLANs supported: 7 | | | |
| | | <ul style="list-style-type: none"> • Network Address Translation (NAT): Port Address Translation (PAT), One-to-one NAT, NAT traversal | | | |
| | | <ul style="list-style-type: none"> • Protocol binding: Protocols can be bound to a specific WAN port for load-balancing purposes | | | |
| | | <ul style="list-style-type: none"> • Network edge (DMZ): DMZ port, DMZ host | | | |
| | | <ul style="list-style-type: none"> • Dual USB 2.0 ports: Storage and 3G/4G modem support | | | |
| | | <ul style="list-style-type: none"> • Firewall: SPI firewall, Denial-of-service (DoS) prevention: ping of death, SYN flood, IP spoofing, WinNuke | | | |
| | | <ul style="list-style-type: none"> • Access rules: Schedule-based access rules, Up to 50 entries | | | |
| | | <ul style="list-style-type: none"> • VLAN: 802.1Q VLAN, 7 VLANs supported | | | |
| | | <ul style="list-style-type: none"> • SSL VPN: 10 SSL VPN tunnels for remote client access | | | |

| | | | | | |
|----|-------------------------|--|---------|--|--|
| | | <ul style="list-style-type: none"> • PPTP: 10 PPTP tunnels for remote access • VPN pass-through: PPTP, Layer 2 Tunneling Protocol (L2TP), Ipsec • Advanced VPN: Dead peer detection (DPD), Split DNS, VPN backup, Internet Key Exchange (IKE) with certificate • IPsec VPN throughput: 100 Mbps • SSL VPN throughput: 20 Mbps • Concurrent connections: 20,000 | | | |
| 11 | Projector | <ul style="list-style-type: none"> • Projection System: 3LCD Technology • LCD Panel: 0.55 inch with D7 • Colour Light Output: 3,200 Lumen- 2,240 Lumen • Resolution: SVGA, 800 x 600, 4:3 • Aspect Ratio: 4:3 • Contrast Ratio: 15,000 : 1 • Lamp: 200 W, 5,000 h durability, 10,000 h durability • Projection Ratio: 1.45 - 1.96:1 • USB Display Function: 3 in 1: Image / Mouse / Sound • USB 2.0 Type A, USB 2.0 Type B, Wireless LAN IEEE 802.11b/g/n (optional), VGA in, HDMI in • Carrying bag, VGA cable, Main unit, Power cable, Remote control incl. batteries, USB cable, User's Manual Set, Warranty Documents | Per Set | | |
| 12 | Projector Screen (Auto) | <ul style="list-style-type: none"> • Projector Screen Motorized 8 * 6 | Per Set | | |

| | | | | | |
|----|-------------------------|--|---------|--|--|
| 13 | Projector Mounting kits | • Projector Mounting kits (Universal) | Per Set | | |
| | | • Lumen 5000, Infocus IN122, InFocus IN2116, Dell 4320 | | | |
| 14 | Network tool kits | • IT-NETTEST Remote Network Tester | Per Set | | |
| | | • IT-CRIMP Modular Crimp Tool | | | |
| | | • IT-STRIP-ECO Economy UTP Stripper | | | |
| | | • NQP-TEL-6090 110 Impact Pro Punch Down Tool w/ Two Blades | | | |
| | | • 30 pieces of RJ-11, RJ-45 Plugs and Boots | | | |
| | | • Zippered black carrying case with handle | | | |
| 15 | Server | • Rack Mount Server (2.5" Chassis with upto 8 Hot Plug Hard Drives) | Per Set | | |
| | | • Intel Xeon E5-2620 V3 2.4GHz, 15M Cache, 8.0GT/s QPI, Turbo, HT, 6C, Max Mem 1866MHz | | | |
| | | • 2 x 8GB RDIMM, 2133 MT/s, Dual Rank, x4 Data Width Memory | | | |
| | | • 2 x 300GB 15K RPM SAS 12 Gbps 2.5in Hot-Plug Hard Drive | | | |
| | | • 6 x 1.2TB 10 RPM SAS 12 Gbps 2.5in Hot-Plug Hard Drive | | | |
| | | • Fully featured Remote Access Port | | | |
| | | • Raid Controller Card with 1GB cache, Raid Level 0, 1, 5, 6; Raid Span 10, 50, 60 support | | | |
| | | • DVD-RW internal | | | |
| | | • Dual PSU | | | |
| | | • On Board Dual 1G Network Ports | | | |
| | | • Server Mangement Softwares and Drivers Disk | | | |
| | | • Preinstalled Windows Server 2008 R2, Installed Linux, Centos | | | |
| | | • Onsite Installation and Configuration Charges as per clients requirement | | | |

| | | | | | |
|----|----------------------|---|----------|--|--|
| 16 | UTP cable (Out door) | • Diglink G600 Cat 6 Copper STP solid cables ,305 m | Per Mtr. | | |
| 17 | Media Converter | • Connector Types: 1x Fiber Optic SC Female | Per set | | |
| | | • 1 x RJ45 Female | | | |
| | | • General Specifications: Supports CAT 5e and CAT6e Ethernet cables | | | |
| | | • Multiple Transmit speed: 10/100Mbps | | | |
| | | • Transmit Fiber: Single-Mode- 8.3/125,8.7/125 or 10/125um | | | |
| | | • Included in package: 1 –Media Converter | | | |
| 18 | Fiber Optic cable | • Brand Name: KNC 6 core fiber optic cable | Per set | | |
| | | • Model Number: 6 core fiber optic cable | | | |
| | | • Number of conductors:> 10 | | | |
| | | • Product Name: 16 core fiber optic cable | | | |
| | | • Installations: By duct, Aerial, direct burial | | | |
| | | • Certificates: ISO:9001, UL, RoHS, CE | | | |
| | | • Outer Jackets: PE,HDPE,PVC, LSZH | | | |
| | | • Fiber Cores: 1 ~ 144 | | | |
| | | • Sheaths: Armored or Kevlar | | | |
| | | • Fiber Types: G. 652, G. 652D, G.651.1 | | | |
| | | • Modes: Single Mode: MultiMode | | | |
| | | • Strength Members: FRP,Steel wire tubes: Loose tube, Tight buffer | | | |

| | | | | | |
|----|--|---|-------------|--|--|
| 19 | Anti virus (Includes installation and configuration) | · Quick Heal Total Security Admin Console | Per package | | |
| | | · 90 users | | | |
| | | · License | | | |
| | | · All new updates can be downloaded for free from internet | | | |
| | | · Up gradation to new version should be will be free | | | |
| | | • Period or 1 and 3 years | | | |
| 20 | CAT 6E cable | · Conductor: Stranded Bare Copper (7 x 32 AWG) | Per Mtr. | | |
| | | · Insulation: HDPE (CMI-75E)Nominal Wall Thickness: 0.178mm | | | |
| | | Min. Thickness: 0.153mm | | | |
| | | · Color Code: Pair 1: Blue & White/Blue | | | |
| | | Pair 2: Orange & White/Orange | | | |
| | | Pair 3: Green & White/Green | | | |
| | | Pair 4: Brown & White/Brown | | | |
| | | · Jacket (Grey): 75°C LSZH Compound Nominal Wall Thickness: 0.585mm | | | |
| | | Min. Thickness: 0.458mm | | | |
| | | Overall Diameter: 5.8mm ± 0.3mm | | | |
| | | · Electric Requirements: Cable length: 100m)Characteristic Impedance(Zo): 85~115Ω (1~250 MHz) | | | |

| | | | | | |
|----|---------------------|---|---------|--|--|
| 21 | RJ45 | • Rj45 | | | |
| 22 | Dell laptop charger | • Dell vostro 3500, Dell vostro 3460, Dell vostro 3550, Dell Inspiron 3421, Dell Latitude E5500, Acer Aspire E1- 471, Dell Inspiron 15 3000 series, Dell Precision M4500, Dell Latitude E5400, Dell Latitude E6540, Dell Latitude E5200, Lenovo Yoga 3, Dell Inspiron N4030, Samsung AITV, Dell XPS, Toshiba, Mac book, Lenovo U41, Dell inspiron 23, Dell XPS 27, lenovo ideapad 500s, Dell Inspiron 14 5000 series, Dell Latitude E5440 | per pcs | | |
| 23 | Laptop battery | • Dell vostro 3500, Dell vostro 3460, Dell vostro 3550, Dell Inspiron 3421, Dell Latitude E5500, Acer Aspire E1- 471, Dell Inspiron 15 3000 series, Dell Precision M4500, Dell Latitude E5400, Dell Latitude E6540, Dell Latitude E5200, Lenovo Yoga 3, Dell Inspiron N4030, Samsung AITV, Dell XPS, Toshiba, Mac book, Lenovo U41,Lenovo ideapad 500s, Dell Inspiron 14 5000 series, Dell Latitude E5440, | per pcs | | |
| 24 | Presenter | • Logitech Wireless Presenter R400 | per pcs | | |
| 25 | T/P basic telephone | • Model: CT-TF232 Brand: Cheeta | per pcs | | |
| 26 | stablizer | • A.C VOLTAGE REGULATOR | per pcs | | |
| | | • MODEL NO:AVR-1500W | Per pcs | | |
| | | • SERVO MOTOR TYPE: | | | |
| | | • Input voltage:AC80V-130V /160V-250V | | | |
| | | • It has high precision 3 second/3 minutes time-delay function. | | | |
| | | • Output voltage AC220V/110V+2% | | | |
| | | • It has over-load indication protection function | | | |

| | | | | | |
|----|---|--|----------|--|--|
| 27 | Back up battery APC SMC1500 1440VA 900W UPS | · 900 Watts /1440 VA | Per pcs | | |
| | | · International Version: 120V | | | |
| | | · Input Voltage Range: 93 - 130V Adjustable range: 85 - 136V | | | |
| | | · Battery Recharge Time: 3 hour(s) | | | |
| | | · Battery Replaceable: RBC6 | | | |
| | | · Alarms: Alarm when on battery : distinctive low battery alarm : configurable delays | | | |
| | | · Interface Port: USB | | | |
| | | · Surge Energy Rating | | | |
| | | · Package Contents: APC Smart-UPS SMC1500 CD with software Documentation CD USB cable | | | |
| 28 | Image Drum | · Printer HP LaserJet CP1025nw: | per set | | |
| | | · Printer Hp Laserjet CP6015dn: CB386A, CB385A,CB387A,CB384A | per set | | |
| | | · Printer Epson stylus photo R3000: | per set | | |
| | | · Printer Epson stylus Pro R3880: | per set | | |
| | | • HP Designjet T770 (Plotter): | per set | | |
| 29 | VGA cable | · 30 m | Per Mtr. | | |
| | | · 40 m | Per Mtr. | | |
| 30 | VGA splitter (Should connect 4 projector using just one laptop) | • Supports over 1600x1280 | Per set | | |
| | | • Duplicates VGA signal to 4 outputs for Multi-Monitors | | | |
| | | • Industrial / Automotive Grade | | | |
| | | • VGA Splitter | | | |
| | | • AC Adaptor | | | |
| | | • Cigarette Lighter Car Adaptor | | | |
| | | • 11~24Volt DC Input | | | |

| | | | | | |
|----|---|---|---------|--|--|
| 31 | Dell XPS 27 (Wireless mouse & wireless key board) | • Dell Premier Wireless Keyboard and Mouse - KM717 | per pcs | | |
| | | • Dell Wireless 3165 802.11AC Wi-Fi + BT 4.0 Wireless Card | per pcs | | |
| 32 | USB mouse | • Windows Vista® or Windows® 7, Windows 8, Windows 10 USB port | Per pcs | | |
| | | • Mac OS® X 10.3.9 or later, USB port | | | |
| | | • Package Contents: Logitech® B100 Optical USB Mouse | | | |
| | | • Technical Specifications: Corded mouse, 3 buttons, USB connectivity, Optical tracking, 800 dpi resolution, Cable: 5-ft 9-in (180 cm) approx, Works with Windows Vista®, Windows® 7, Windows 8, Windows 10 | | | |
| 33 | Wireless mouse | • Windows Vista®, Windows® 7, Windows 8, Windows 10 | Per Pcs | | |
| | | • Mac OS® X 10.5 or later | | | |
| | | • Package Contents: Mouse, Nano receiver, 1 AA battery (pre-installed) | | | |
| | | • Technical Specifications: Mouse Dimensions (height x width x depth): 2.36 in (60 mm) x 3.89 in (99 mm) x 1.54 in (39 mm) | | | |
| | | • Sensor technology: Advanced Optical Tracking | | | |
| | | • Sensor Resolution: 1000 | | | |
| | | • Number of buttons: 3 | | | |
| | | • Scroll Wheel (Y/N): Yes | | | |
| | | • Battery life: 12-month battery life* | | | |
| | | • Battery type: 1 AA battery | | | |
| | | • Wireless operating distance: Approx 10m* | | | |
| | | • Wireless technology: Advanced 2.4 GHz wireless connectivity | | | |
| | | • Supported OS: Windows Vista, Windows 7, Windows 8, Windows 10, Mac OS X 10.5 or later | | | |

| | | | | | |
|----|-------------|---|---------|--|--|
| 34 | Maintenance | • Dell vostro 3500, Dell vostro 3460, Dell vostro 3550, Dell Inspiron 3421, Dell Latitude E5500, Acer Aspire E1- 471, Dell Inspiron 15 3000 series, Dell Precision M4500, Dell Latitude E5400, Dell Latitude E6540, Dell Latitude E5200, Lenovo Yoga 3, Dell Inspiron N4030, Samsung AITV, Dell XPS, Toshiba, Mac book, Lenovo U41, Dell inspiron 23, Dell XPS 27, lenovo ideapad 500s, Dell Inspiron 14 5000 series, Dell Latitude E5440 | Per pcs | | |
| | | • Desktop: Dell Optiplex 330, Dell Optiplex 360, Acer, Dell Optiplex 170L, Hp Elite/ HPdvd 1260, Lenovo, Dell Vostor 220s, Dell Precision T7500 (Work Station), Dell Inspiron 660s, Dell Inspiron 23, Dell XPS 27, Workstation Dell Precision tower 7910 | per pcs | | |
| | | • Printer: Hp Laserjet 3005n, HP Laserjet 1320, Hp Laserjet 1006, Panasonic KX- MB772, SHARP AR-M201, Hp Laserjet 2055dn, HP laserjet M1213n, Hp laserjet CP6015dn (Color), Hp Laserjet CP1025nw (Color), Epson Stylus Photo R3000, Xerox workstation 5755, Sharp AR-5726, WC 5755, Sharp AR 3726, Hp Laserjet 3005n | per pcs | | |
| | | • Scanner: Hp Scanjet G2410, Epson Perfection 1640SU, HP Scanjet G3010 | per pcs | | |
| | | • Projector: NEC NP510, InFocus IN2116, Espon EMP S5, Lumen 5000, Infocus IN122 | per pcs | | |
| | | • Lamination: Gobbler GML-30 | per pcs | | |
| | | • Fax: Panasonic KX-FP107 | per pcs | | |
| | | • Server: Dell power edge 2950 | per pcs | | |
| | | • Server: Dell power edge r530 | per pcs | | |
| | | • Server: System X3100 M4 | per pcs | | |